



EMF Assessment Report

EN 62479:2010

For

Applicant: SHENZHEN MARK TRADING CO., LTD.

Address: 6th Floor, Building A, DongFangYaYuan, Chen Tian Communities,
Xixiang Bao'an District, Shenzhen, China

Product Name: Wireless Game pad

Model Name: GT-60, GT-***, GP-***, EGC-***(**stand for 0-9) (**stand for 0-9)

Brand Name: MARVO, XTRIKE ME, @ONE

Report No.: MTWN19070322

Date of Issue: Jul.29, 2019

Issued by : Shenzhen Most Technology Service Co., Ltd..

Address : No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,
Nanshan, Shenzhen, Guangdong, China

Tel : 86-755-86026850

Fax : 86-755-26013350



The report consists 9 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

CONTENTS

1.	TEST RESULT CERTIFICATION	3
2.	Technical Information.....	4
2.1	EUT Description	4
2.2	Objective	5
2.3	Test Standards and Results	5
3.	Details of Test.....	6
3.1	Identification of the Responsible Testing Laboratory	6
3.2	Identification of the Responsible Testing Location	6
3.3	Description of Test Modes	6
3.4	Environmental Conditions	6
3.5	Measurement Uncertainty	7
4.	EN 62479 requirements.....	8
4.1	Human Exposure to the Electromagnetic Fields	8

1. TEST RESULT CERTIFICATION

Applicant Name:	SHENZHEN MARK TRADING CO., LTD.
Address:	6th Floor, Building A, DongFangYaYuan, Chen Tian Communities, Xixiang Bao'an District, Shenzhen, China
Manufacturer Name:	SHENZHEN MARK TRADING CO., LTD.
Address:	6th Floor, Building A, DongFangYaYuan, Chen Tian Communities, Xixiang Bao'an District, Shenzhen, China
Equipment Under Test:	Wireless Game pad
Brand Name:	MARVO, XTRIKE ME, @ONE
Model Number:	GT-60
Series Model Number:	GT-***, GP-***, EGC-***(**stand for 0-9) (**stand for 0-9)
Difference description:	Only difference in model names
Test Standard	EN 62479:2010
File Number:	MTWN19070322
Date of Test:	Jul.24-26, 2019

We (MOST) for compliance with the requirements set forth in the European Standard EN 62479:2010. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested by (+ signature):

Lili Lu

Lili Lu (Engineer)

Jul.24-26, 2019

Review by (+ signature):

Sunny

Sunny Deng (Engineer)

Jul.29, 2019



Approved by (+ signature):

Yvette Zhou

Yvette Zhou(Manager)

Jul.29, 2019

2. Technical Information

Note: the following data is based on the information by the applicant.

2.1 EUT Description

Product	Wireless Game pad
Trade Name	MARVO
Model Number	GT-60
Power Supply	DC 5V by USB Port DC 3.7V by Battery
Frequency Range	2402-2480MHz for BT3.0
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK for FHSS
Channel Number	79 for BT3.0
Extreme Temperature:	-20°C ~ +55° C

Note:

1. For more details, please refer to the User's manual of the EUT.

2.2 Objective

EUT Satisfy RED Directive 2014/53/EU - Article 3.1(a), Ref LVD Directive 2014/35/EU- Article 3, 12

2.3 Test Standards and Results

The EUT has been tested according to EN 62479:2010

EN 62479:2010	Assessment of the compliance of low power electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (10MHz – 300GHz)
---------------	--

Test items and the results are as bellow:

No	Basic Standard	Test Result
1	EN 62479:2010	PASS

3. Details of Test

3.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Most Technology Service Co., Ltd.
Address:	No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China

3.2 Identification of the Responsible Testing Location

Test Site:	Shenzhen Most Technology Service Co., Ltd.
Address:	No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China
Description:	There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4 and CISPR 16 requirements. The FCC Registration Number is 490827 . The CNAS Registration Number is CNAS L3573 .

3.3 Description of Test Modes

The EUT had been tested under the operating condition. There are three modulation have been tested as following:

Mode	Frequency (MHz)
BT 3.0	2402

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed. The field strength of spurious emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis) with adapter respectively. The worst emission was found in stand-up position (Y axis).

3.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 k Pa

3.5 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in Measurement” (GUM) published by ISO.

- Uncertainty of Conducted Emission, $U_c = \pm 1.8\text{dB}$
- Uncertainty of Radiated Emission, $U_c = \pm 3.2\text{dB}$

4. EN 62479 requirements

4.1 Human Exposure to the Electromagnetic Fields

4.1.1. LIMIT

Low-power exclusion level(P_{\max})

Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to applicable low-power exclusion level P_{\max} .

Low-power exclusion level P_{\max} based on considerations of SAR

When SAR is the basic restriction, a conservative minimum value for P_{\max} can be derived, equal to the localized SAR limit (SAR_{\max}) multiplied by the averaging mass (m):

$$P_{\max} = SAR_{\max} m \quad (\text{A.1})$$

Example values of P_{\max} according to Equation (A.1) are provided in Table A.1 for cases described by the ICNIRP guidelines [1], IEEE Std C95.1-1999 [2] and IEEE Std C95.1-2005 [3] where SAR limits are defined. Other exposure guidelines or standards may be applicable depending on national regulations.

Table A.1 – Example values of SAR-based P_{\max} for some cases described by ICNIRP, IEEE Std C95.1-1999 and IEEE Std C95.1-2005

Guideline / Standard	SAR limit, SAR_{\max} W/kg	Averaging mass, m g	P_{\max} mW	Exposure tier ^a	Region of body ^a
ICNIRP [1]	2	10	20	General public	Head and trunk
	4	10	40	General public	Limbs
	10	10	100	Occupational	Head and trunk
	20	10	200	Occupational	Limbs
IEEE Std C95.1-1999 [2]	1,6	1	1,6	Uncontrolled environment	Head, trunk, arms, legs
	4	10	40	Uncontrolled environment	Hands, wrists, feet and ankles
	8	1	8	Controlled environment	Head, trunk, arms, legs
	20	10	200	Controlled environment	Hands, wrists, feet and ankles
IEEE Std C95.1-2005 [3]	2	10	20	Action level	Body except extremities and pinnae
	4	10	40	Action level	Extremities and pinnae
	10	10	100	Controlled environment	Body except extremities and pinnae
	20	10	200	Controlled environment	Extremities and pinnae

^a Consult the appropriate standard for more information and definitions of terms.

4.1.2. conformity assessment methods

Compliance of electromagnetic emissions from electronic and electrical equipment with the basic restrictions usually is determined by measurements and, in some cases, calculation of the exposure level. If the electrical power used by or radiated by the equipment is sufficiently low, the electromagnetic fields emitted will be incapable of producing exposures that exceed the basic restrictions. This standard provides simple EMF assessment procedures for this low power equipment.

4.1.3. Test Results

Modulation	EPR/EIRP	ERP/EIRP	Limit	Result
type	dBm	mW	mW	Pass/Fail
GFSK	0.82	1.208	20	PASS

Since average output power at worse case is: 1.208mW, which cannot exceed the exempt condition, 20mW specified in EN 62479.

*** End of the Reports***